

# SETA 60 CONEX reflector

## direct plug / socket

surface / suspended system  
058-4028137R




Project / Type
Notes
Count / Date



Luminaire housing made of extruded aluminium profile; extremely slim design (only Ø 60 mm) linear; converter integrated into luminaire housing; for lighting systems; surface white powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension - oblique or straight - as an accessory); easy installation using ceiling clips (available as an accessory) or with integrated toolless suspension height adjustment on the luminaire; canopy for through wiring (available as an accessory); electrical connection of the luminaires via plug/socket system; connectors (L-, T- or X-shape) available as an accessory; luminaire connection rotatable around its own axis, which means that any spatial angle can be realized; extruded profile for improved thermal management; high gloss reflector with faceted design;  $UGR \leq 19$ ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above  $65^\circ \leq 1500 \text{ cd/m}^2$ ; light colour 4000 K; binning initial MacAdam  $\leq 3 \text{ SDCM}$ ;  $CRI \geq 90$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Light distribution



### Product drawing



### General

Ceiling , Suspended
white , RAL 9010 <sup>1</sup>
chrome
IP20
5750 lm

### LED

4000 K
$CRI \geq 90$
L90 / 50000 h
initial MacAdam $\leq 3 \text{ SDCM}$
$R_g: 99, R_r: 92, R_{f(1-15)}: 90$
MR 0.81
MDER 0.74

### Optical

Reflector
symmetric
$UGR \leq 19, \geq 65^\circ \leq 1500 \text{ cd/m}^2$
$PstLM \leq 1.0$ <sup>2</sup>
$SVM \leq 0.4$ <sup>2</sup>

### Electrical

DALI-2
220-240 V
system 43 W
system 134 lm/W <sup>3</sup>
PC1
1 DALI Addr.

### Physical

length 2351 mm
width 60 mm
height 60 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

### Installation instructions



### Lighting calculator

