

# MICRO 10

recessed  
011-8100118S



Project / Type

Notes

Count / Date



General

Showcase , Recessed

black , RAL9021 <sup>1</sup>

IP20

Interior

62 lm

LED

4000 K

CRI ≥ 95

L80 / 50000 h

photobio. safety RG 1 - low Risk

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 94 , R<sub>f(1-5)</sub>: 96

MR 0.87

MDER 0.78

Optical

spot

beam angle 18°

Electrical

excl. driver

system 1.4 W

inset 1.1 W


350 mA

PC3

inset 58 lm/W<sup>2</sup>

Round recessed spotlight in aluminium; surface lacquered in black; with trim; suitable for ceiling thickness of 10-20 mm; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 18° beam; degree of protection IP20; PC3; photobiological safety according to IEC 62471 risk group RG 1 - low Risk; plug and play electrical connector system for toolless mounting (available as an accessory); accessories are listed separately; light source replaceable by an authorized professional;


Light distribution



spot 18°

h (m)	E0° (lx)	ø (m)
1	453	0.32
2	113	0.64
3	50	0.96
4	28	1.28
5	18	1.59

Product drawing



Physical

length 20 mm

width 20 mm

height 33 mm

Cutout

min. ceiling thickness 10 mm

max. ceiling thickness 20 mm

<sup>1</sup> RAL code <sup>2</sup> incl. optical losses

Installation instructions



# MICRO 10

recessed  
011-8100118S



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.954	0.915	0.879	0.844	0.81
LSF	1	1	1	1	1

MF

LMF × RSMF × LLMF × LSF

MF

Maintenance Factor

LMF<sup>a</sup>

Luminaire Maintenance Factor

RSMF<sup>a</sup>

Room Surface Maintenance Factor

LLMF

Lamp Lumens Maintenance Factor

LSF

Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Electrical accessories

### POWER SUPPLY 24V EU

TYPE	L·W·H (MM)	ARTICLE NUMBER(S)
9 W   non dim	115-19-34	011-9211110
15 W   DALI-2	145-33-21	011-9211130

### POWER SUPPLY 24V UL

TYPE	L·W·H (MM)	ARTICLE NUMBER(S)
9 W   non dim	115-19-34	011-9281110

## Electrical accessories

### SPLITTER SERIAL

TYPE	L·W·H (MM)	ARTICLE NUMBER(S)
3 × socket / 1 × plug	38-30-10	011-9228300
6 × socket / 1 × plug	55-32-10	011-9228600

## Electrical accessories

### EXTENSION CABLE

TYPE	ARTICLE NUMBER(S)
1 × socket / 1 × plug	011-9221120
1 × socket / 1 × plug	011-9221140
1 × socket / 1 × plug	011-9221180

