

# MICRO 10

recessed  
011-8100116F



Project / Type

Notes

Count / Date



General

Showcase , Recessed

white aluminium , RAL9006 <sup>1</sup>

IP20

Interior

101 lm

LED

4000 K

CRI ≥ 95

L85 / 50000 h

photobio. safety RG 1 - low Risk

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 94 , R<sub>f(1-5)</sub>: 96

MR 0.87

MDER 0.78

Optical

flood

beam angle 39°

Electrical

excl. driver

system 1.4 W

inset 1.0 W

350 mA

PC3

inset 99 lm/W<sup>2</sup>

Physical

length 20 mm

width 20 mm

height 33 mm


Cutout

min. ceiling thickness 10 mm

max. ceiling thickness 20 mm

<sup>1</sup> RAL code <sup>2</sup> incl. optical losses


Light distribution



flood 39°

h (m)	E0° (lx)	ø (m)
1	206	0.71
2	51	1.42
3	23	2.13
4	13	2.84
5	8	3.55

Product drawing



Installation instructions



[‘011-8100116F’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

# MICRO 10

recessed  
011-8100116F



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.983	0.957	0.931	0.906	0.881
LSF	1	1	1	1	1

MF

MF

LMF<sup>a</sup>

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF<sup>a</sup>

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Electrical accessories

### POWER SUPPLY 24V EU

TYPE	L·W·H (MM)	ARTICLE NUMBER(S)
9 W   non dim	115-19-34	011-9211110
15 W   DALI-2	145-33-21	011-9211130

### POWER SUPPLY 24V UL

TYPE	L·W·H (MM)	ARTICLE NUMBER(S)
9 W   non dim	115-19-34	011-9281110

## Electrical accessories

### SPLITTER SERIAL

TYPE	L·W·H (MM)	ARTICLE NUMBER(S)
3 × socket / 1 × plug	38-30-10	011-9228300
6 × socket / 1 × plug	55-32-10	011-9228600

## Electrical accessories

### EXTENSION CABLE

TYPE	ARTICLE NUMBER(S)
1 × socket / 1 × plug	011-9221120
1 × socket / 1 × plug	011-9221140
1 × socket / 1 × plug	011-9221180

