

MICRO 10

recessed
011-8100018F



Project / Type

Notes

Count / Date



General

Showcase , Recessed

black , RAL9021¹

IP20

Interior

93 lm

LED

3000 K

CRI ≥ 95

L85 / 50000 h

photobio. safety RG 1 - low Risk

initial MacAdam ≤ 3 SDCM

R_g: 102 , R_f: 94 , R_{f(1-5)}: 95

MR 0.61

MDER 0.55

Optical

flood

beam angle 39°

Electrical

excl. driver

system 1.3 W

inset 0.9 W

350 mA

PC3

inset 98 lm/W²

Physical

length 20 mm

width 20 mm

height 33 mm


Cutout

min. ceiling thickness 10 mm

max. ceiling thickness 20 mm

¹ RAL code ² incl. optical losses


Light distribution



flood 39°

h (m)	EO ² (lx)	ø (m)
1	189	0.71
2	47	1.42
3	21	2.13
4	12	2.84
5	8	3.55

Product drawing



Installation instructions



[“011-8100018F”] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

MICRO 10

recessed

011-8100018F



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.983	0.957	0.931	0.906	0.881
LSF	1	1	1	1	1

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Electrical accessories

POWER SUPPLY 24V EU

TYPE	L·W·H (MM)	ARTICLE NUMBER(S)
9 W non dim	115-19-34	011-9211110
15 W DALI-2	145-33-21	011-9211130

POWER SUPPLY 24V UL

TYPE	L·W·H (MM)	ARTICLE NUMBER(S)
9 W non dim	115-19-34	011-9281110

Electrical accessories

SPLITTER SERIAL

TYPE	L·W·H (MM)	ARTICLE NUMBER(S)
3 × socket / 1 × plug	38-30-10	011-9228300
6 × socket / 1 × plug	55-32-10	011-9228600

Electrical accessories

EXTENSION CABLE

TYPE	ARTICLE NUMBER(S)
1 × socket / 1 × plug	011-9221120
1 × socket / 1 × plug	011-9221140
1 × socket / 1 × plug	011-9221180

