

MICRO 10

recessed

011-8100016M



Project / Type


Notes

Count / Date



Round recessed spotlight in aluminium; surface lacquered in white aluminium; with trim; suitable for ceiling thickness of 10-20 mm; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 30° beam; degree of protection IP20; PC3; plug and play electrical connector system for toolless mounting (available as an accessory); accessories are listed separately; light source replaceable by an authorized professional;


Light distribution



medium 30°

h (m)	E0° (lx)	ø (m)
1	280	0.54
2	70	1.07
3	31	1.61
4	18	2.15
5	11	2.68

Product drawing



General

Showcase , Recessed

white aluminium , RAL 9006 ¹

IP20

Interior

92 lm

fixture 97 lm/W²

LED

3000 K

CRI ≥ 95

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 102 , R_f: 94 , R_{f(1-15)}: 95

MR 0.61

MDER 0.55

Optical

medium

beam angle 30°

Electrical

excl. driver

fixture 0.9 W

350 mA

PC3

Physical

length 20 mm

width 20 mm

height 33 mm

Cutout

min. ceiling thickness 10 mm

max. ceiling thickness 20 mm

¹ RAL code

² incl. consideration of optical losses & internal control unit losses

Installation instructions



MICRO 10

recessed

011-8100016M



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.983	0.957	0.931	0.906	0.881
LSF	1	1	1	1	1

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Electrical accessories

POWER SUPPLY EU

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
15 W DALI-2	145-33-21	011-9211130



Electrical accessories

SPLITTER SERIAL

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
3 × socket / 1 × plug	38-30-10	011-9228300
6 × socket / 1 × plug	55-32-10	011-9228600



Electrical accessories

EXTENSION CABLE

TYPE	ARTICLE NUMBER(S)
1 × socket / 1 × plug	011-9221120
1 × socket / 1 × plug	011-9221140
1 × socket / 1 × plug	011-9221180

