

# STADIO 10

semi-recessed  
011-8000118M



Project / Type

Notes

Count / Date



General

Showcase , Surface

tilt max 90°

rotation 360°

black , RAL9021<sup>1</sup>

IP20

Interior

65 lm

LED

4000 K

CRI ≥ 95

L85 / 50000 h

photobio. safety RG 1 - low Risk

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 94 , R<sub>{1-15}</sub>: 96

MR 0.87

MDER 0.78


Optical

medium

beam angle 30°


Cylindrical semi-recessed mounted spotlight miniature spotlight made of aluminium; surface lacquered in black; spotlight head 360° rotatable and 90° tiltable; suitable for ceiling thickness of 12.5-22 mm; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 30° beam; degree of protection IP20; PC3; photobiological safety according to IEC 62471 risk group RG 1 - low Risk; plug and play electrical connector system for toolless mounting (available as an accessory); accessories are listed separately; light source replaceable by an authorized professional;

## Light distribution



medium 30°		
h (m)	EO° (lx)	ø (m)
1	198	0.54
2	49	1.07
3	22	1.61
4	12	2.15
5	8	2.68

## Product drawing



Electrical

excl. driver

system 0.8 W

inset 0.6 W

220 mA

PC3

inset 105 lm/W<sup>2</sup>

200 mA

Physical

length 11 mm

width 11 mm

height 29 mm

Cutout

min. ceiling thickness 12.5 mm

max. ceiling thickness 22 mm

<sup>1</sup> RAL code <sup>2</sup> incl. optical losses

## Installation instructions

