

STADIO 10

semi-recessed
011-8000118F



Project / Type _____

Notes _____

Count / Date _____



General

Showcase , Surface _____

tilt max 90° _____

rotation 360° _____

black , RAL 9021 ¹ _____

IP20 _____

Interior _____

66 lm _____

fixture 106 lm/W² _____

LED

4000 K _____

CRI ≥ 95 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 100 , R_f: 94 , R_{1-15}: 96 _____

MR 0.87 _____

MDER 0.78 _____


Optical

flood _____

beam angle 39° _____

Cylindrical semi-recessed mounted spotlight miniature spotlight made of aluminium; surface lacquered in black; spotlight head 360° rotatable and 90° tiltable; suitable for ceiling thickness of 12.5-22 mm; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 39° beam; degree of protection IP20; PC3; plug and play electrical connector system for toolless mounting (available as an accessory); accessories are listed separately; light source replaceable by an authorized professional;


Light distribution



flood 39°

h (m)	EO ² (lx)	ø (m)
1	134	0.71
2	34	1.42
3	15	2.13
4	8	2.84
5	5	3.55

Product drawing



Electrical

excl. driver _____

fixture 0.6 W _____

220 mA _____

PC3 _____

200 mA _____

Physical

length 11 mm _____

width 11 mm _____

height 29 mm _____

Cutout

min. ceiling thickness 12.5 mm _____

max. ceiling thickness 22 mm _____

¹ RAL code
² incl. consideration of optical losses & internal control unit losses

Installation instructions



STADIO 10

semi-recessed
011-8000118F



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.983	0.957	0.931	0.906	0.881
LSF	1	1	1	1	1

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Electrical accessories

POWER SUPPLY EU

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
15 W DALI-2	145-33-21	011-9211130



Electrical accessories

SPLITTER SERIAL

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
3 × socket / 1 × plug	38-30-10	011-9228300
6 × socket / 1 × plug	55-32-10	011-9228600



Electrical accessories

EXTENSION CABLE

TYPE	ARTICLE NUMBER(S)
1 × socket / 1 × plug	011-9221120
1 × socket / 1 × plug	011-9221140
1 × socket / 1 × plug	011-9221180

