

# STADIO 10

semi-recessed  
011-8000018F



Project / Type


Notes

Count / Date




Cylindrical semi-recessed mounted spotlight miniature spotlight made of aluminium; surface lacquered in black; spotlight head 360° rotatable and 90° tiltable; suitable for ceiling thickness of 12.5-22 mm; light colour 3000 K; CRI ≥ 95; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 39° beam; degree of protection IP20; PC3; plug and play electrical connector system for toolless mounting (available as an accessory); accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



flood 39°			
h (m)	E0° (lx)	ø (m)	
1	122	0.71	
2	31	1.42	
3	14	2.13	
4	8	2.84	
5	5	3.55	

## Product drawing



### General

Showcase , Surface

tilt max 90°

rotation 360°

black , RAL9021<sup>1</sup>

IP20

Interior

60 lm

### LED

3000 K

CRI ≥ 95

### Optical

flood

beam angle 39°

### Electrical

excl. driver

24 V

0.8 W

inset 0.6 W

220 mA

PC3

75 lm/W

200 mA

### Physical

length 11 mm

width 11 mm

height 29 mm

### Cutout

min. ceiling thickness 12.5 mm

max. ceiling thickness 22 mm

<sup>1</sup> RAL code

## Installation instructions



# STADIO 10

semi-recessed  
011-8000018F



Project / Type

Notes

Count / Date

## Electrical accessories

### POWER SUPPLY 24V EU

L·W·H (MM)	ARTICLE NUMBER(S)
115-19-34	011-9211110
145-33-21	011-9211130

### POWER SUPPLY 24V UL

L·W·H (MM)	ARTICLE NUMBER(S)
115-19-34	011-9281110

## Electrical accessories

### SPLITTER SERIAL

L·W·H (MM)	ARTICLE NUMBER(S)
38-30-10	011-9228300
55-32-10	011-9228600

## Electrical accessories

### EXTENSION CABLE

TYPE	ARTICLE NUMBER(S)
1 × socket / 1 × plug	011-9221120
1 × socket / 1 × plug	011-9221140
1 × socket / 1 × plug	011-9221180

