

STADIO 10

semi-recessed
011-8000018F



Project / Type _____


Notes _____

Count / Date _____



Cylindrical semi-recessed mounted spotlight miniature spotlight made of aluminium; surface lacquered in black; spotlight head 360° rotatable and 90° tiltable; suitable for ceiling thickness of 12.5-22 mm; light colour 3000 K; CRI ≥ 95; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 39° beam; degree of protection IP20; PC3; plug and play electrical connector system for toolless mounting (available as an accessory); accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



flood 39°

h (m)	E0° (lx)	ø (m)
1	122	0.71
2	31	1.42
3	14	2.13
4	8	2.84
5	5	3.55

Product drawing



General

Showcase , Surface _____

tilt max 90° _____

rotation 360° _____

black , RAL9021¹ _____

IP20 _____

Interior _____

60 lm _____

LED

3000 K _____

CRI ≥ 95 _____

Optical

flood _____

beam angle 39° _____

Electrical

excl. driver _____

24 V _____

0.8 W _____

inset 0.6 W _____

220 mA _____

PC3 _____

75 lm/W _____

200 mA _____

Physical

length 11 mm _____

width 11 mm _____

height 29 mm _____

Cutout

min. ceiling thickness 12.5 mm _____

max. ceiling thickness 22 mm _____

¹ RAL code

Installation instructions



[011-8000018F] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com