

STADIO 10

semi-recessed
011-8000016F



Project / Type

Notes

Count / Date



General

Showcase , Surface

tilt max 90°

rotation 360°

white aluminium , RAL 9006 ¹

IP20

Interior

60 lm

fixture 105 lm/W²

LED

3000 K

CRI ≥ 95

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 102 , R_f: 94 , R_{f(1-5)}: 95

MR 0.61

MDER 0.55


Optical

flood

beam angle 39°


Cylindrical semi-recessed mounted spotlight miniature spotlight made of aluminium; surface lacquered in white aluminium; spotlight head 360° rotatable and 90° tiltable; suitable for ceiling thickness of 12.5-22 mm; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 39° beam; degree of protection IP20; PC3; plug and play electrical connector system for toolless mounting (available as an accessory); accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



flood 39°			
h (m)	EO° (lx)	ø (m)	
1	122	0.71	
2	31	1.42	
3	14	2.13	
4	8	2.84	
5	5	3.55	

Product drawing



Electrical

excl. driver

fixture 0.6 W

220 mA

PC3

200 mA

Physical

length 11 mm

width 11 mm

height 29 mm

Cutout

min. ceiling thickness 12.5 mm

max. ceiling thickness 22 mm

¹ RAL code
² incl. consideration of optical losses & internal control unit losses

Installation instructions

