



Project / Type _____


Notes _____

Count / Date _____



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); equipped with miniature spotlight heads; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 30° beam; light inset rotatable; degree of protection IP20; PC3 24V; accessories are listed separately;


Light distribution



medium 30°

h (m)	E0° (lx)	ø (m)
1	1090	0.54
2	270	1.07
3	120	1.61
4	70	2.15
5	40	2.68

Product drawing



General

Showcase , Standing _____

rotation 360° _____

white aluminium , RAL9006 ¹ _____

IP20 _____

Interior _____

358 lm _____

LED

4000 K _____

CRI ≥ 95 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 100 , R_f: 94 , R_{f(1-5)}: 96 _____

MR 0.87 _____

MDER 0.78 _____

Optical

medium _____

beam angle 30° _____

Electrical

excl. driver _____

24 V _____

4.5 W _____

PC3 24V _____

80 lm/W _____

Physical

length 400 mm _____

width 11 mm _____

height 29 mm _____

¹ RAL code

Installation instructions

