



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



**General**

Showcase , Standing \_\_\_\_\_

rotation 360° \_\_\_\_\_

white aluminium , RAL9006 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

330 lm \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_

CRI ≥ 95 \_\_\_\_\_

**Optical**

medium \_\_\_\_\_

beam angle 30° \_\_\_\_\_

**Electrical**

excl. driver \_\_\_\_\_

24 V \_\_\_\_\_

4.2 W \_\_\_\_\_

PC3 24V \_\_\_\_\_

79 lm/W \_\_\_\_\_

**Physical**


length 400 mm \_\_\_\_\_

width 11 mm \_\_\_\_\_

height 29 mm \_\_\_\_\_

Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); equipped with miniature spotlight heads; light colour 3000 K; CRI ≥ 95; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 30° beam; light inset rotatable; degree of protection IP20; PC3 24V; accessories are listed separately;


Light distribution



medium 30°

h (m)	E0° (lx)	ø (m)
1	1000	0.54
2	250	1.07
3	110	1.61
4	60	2.15
5	40	2.68

Product drawing



<sup>1</sup> RAL code

Installation instructions

