



Project / Type _____

Notes _____

Count / Date _____



General

Showcase , Recessed
 tilt max 90°
 rotation 360°
 white aluminium , RAL 9006 ¹
 IP20
 Interior
 330 lm
 optical inset 18 lm/W²

LED

3000 K
 CRI ≥ 95
 L85 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 102 , R_r: 94 , R_{f(15)}: 95
 MR 0.61
 MDER 0.55

Optical

medium
 beam angle 30°

Electrical

excl. driver
 24 V
 fixture 4.7 W
 optical inset 3.1 W
 PC3
 24 V

Physical

length 400 mm
 width 11 mm
 height 29 mm

¹ RAL code


² OPTICAL INSET: incl. consideration of optical losses

Installation instructions



Miniature linear light inset made of aluminium; tubular design; surface lacquered in white aluminium; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); equipped with miniature spotlight heads; spotlight heads 360° rotatable and 90° tilttable; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 30° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



medium 30°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 167 | 0.54 |
| 2 | 42 | 1.07 |
| 3 | 19 | 1.61 |
| 4 | 10 | 2.15 |
| 5 | 7 | 2.68 |

Product drawing

