

FINA SUPPORT spot line

30°

011-0307018A



Project / Type

Notes

Count / Date



General

Showcase , Standing

rotation 360°

black , RAL 9021 ¹

IP20

Interior

1150 lm

optical inset 71 lm/W²

LED

3000 K

CRI ≥ 95

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 102 , R_r: 94 , R_{f(1-15)}: 95

MR 0.61

MDER 0.55

Optical

asymmetric

Electrical

excl. driver

24 V

fixture 24.1 W

optical inset 16.1 W

PC3

21 W/m

24 V

Physical

length 1200 mm

width 9 mm

height 9 mm

¹ RAL code


² OPTICAL INSET: incl. consideration of optical losses

Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

