

FINA SUPPORT lead 30°

011-1306116A



Project / Type

Notes

Count / Date



General

Showcase , Standing

rotation 360°

white aluminium , RAL9006 ¹

IP20

Interior

1280 lm

LED

4000 K

CRI ≥ 97

L85 / 50000 h

photobio. safety RG 1 - low Risk

initial MacAdam ≤ 3 SDCM

R_g: 100 , R_f: 96 , R_{f(1-15)}: 98

MR 0.86

MDER 0.78

Optical

asymmetric

Electrical

excl. driver

24 V

system 18.2 W

PC3 24V

inset 92 lm/W²

19 W/m

24 V

Physical


length 1000 mm

width 9 mm

height 9 mm

¹ RAL code ² incl. optical losses

Light distribution



Product drawing



Installation instructions



[‘011-1306116A’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com