

FINA SUPPORT spot line

30°

011-0307016A



Project / Type

Notes

Count / Date



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3 24V; photobiological safety according to IEC 62471 risk group RG 1 - low Risk; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase , Standing

rotation 360°

white aluminium , RAL9006 ¹

IP20

Interior

1150 lm

LED

3000 K

CRI ≥ 95

L80 / 50000 h

photobio. safety RG 1 - low Risk

initial MacAdam ≤ 3 SDCM

R_g: 102 , R_r: 94 , R₍₁₋₁₅₎: 95

MR 0.61

MDER 0.55

Optical

asymmetric

Electrical

excl. driver

24 V

system 24.1 W

PC3 24V

inset 71 lm/W²

21 W/m

24 V

Physical

length 1200 mm

width 9 mm

height 9 mm

¹ RAL code ² incl. optical losses

Installation instructions



FINA SUPPORT spot line

30°

011-0307016A



Project / Type

Notes

Count / Date

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|--------|--------|--------|--------|--------|
| LLMF | 0.954 | 0.915 | 0.879 | 0.844 | 0.81 |
| LSF | 1 | 1 | 1 | 1 | 1 |

MF

LMF × RSMF × LLMF × LSF

MF

Maintenance Factor

LMF^a

Luminaire Maintenance Factor

RSMF^a

Room Surface Maintenance Factor

LLMF

Lamp Lumens Maintenance Factor

LSF

Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Mounting accessories

MOUNTING POLE T

| TYPE | COLOUR | ARTICLE NUMBER(S) |
|-------------------------------|-----------------|-------------------|
| mechanical / electrical 180 | white aluminium | 011-9122126 |
| mechanical / electrical 180 | black | 011-9122128 |
| mechanical / electrical 200 | white aluminium | 011-9122226 |
| mechanical / electrical 200 | black | 011-9122228 |
| mechanical / electrical 300 | white aluminium | 011-9122326 |
| mechanical / electrical 300 | black | 011-9122328 |

