

# FINA SUPPORT spot line

## 30°

011-0304118A



Project / Type


Notes

Count / Date



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 95$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3 24V; photobiological safety according to IEC 62471 risk group RG 1 - low Risk; accessories are listed separately; light source replaceable by an authorized professional;

### Light distribution



### Product drawing



### General

Showcase , Standing

rotation 360°

black , RAL9021 <sup>1</sup>

IP20

Interior

634 lm

### LED

4000 K

CRI  $\geq 95$

L80 / 50000 h

photobio. safety RG 1 - low Risk

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 92 , R<sub>(1-15)</sub>: 89

MR 0.76

MDER 0.69

### Optical

asymmetric

### Electrical

excl. driver

24 V

system 12.2 W

PC3 24V

inset 78 lm/W<sup>2</sup>

22 W/m

24 V

### Physical

length 600 mm

width 9 mm

height 9 mm

<sup>1</sup> RAL code <sup>2</sup> incl. optical losses

### Installation instructions

