

FINA SUPPORT spot line 30°

011-0303116M



Project / Type

Notes

Count / Date



General

Showcase , Standing

rotation 360°

white aluminium , RAL 9006 ¹

IP20

Interior

478 lm

optical inset 88 lm/W²

LED

4000 K

CRI ≥ 95

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_r: 92 , R₍₁₋₁₅₎: 89

MR 0.76

MDER 0.69

Optical

medium

beam angle 32°x46°

Electrical

excl. driver

24 V

fixture 8.1 W

fixture 59 lm/W³

optical inset 5.4 W

PC3

24 V

Physical


length 400 mm

width 9 mm

height 9 mm

Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; precise radiation characteristic with 32°x46° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code

² OPTICAL INSET: incl. consideration of optical losses

³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions

