



Project / Type

Notes

Count / Date



General
Showcase , Standing
rotation 360°
white aluminium , RAL9006 ¹
1310 lm/m
IP20
Interior
1280 lm

LED
4000 K
CRI ≥ 97
L85 / 50000 h
photobio. safety RG 1 - low Risk
initial MacAdam ≤ 3 SDCM
R _g : 100 , R _f : 96 , R _{f(1-15)} : 98
MR 0.86
MDER 0.78

Optical
asymmetric

Electrical
excl. driver
24 V
system 18.2 W
PC3 24V
inset 92 lm/W ²
19 W/m
24 V

Physical
length 1000 mm
width 9 mm
height 9 mm


¹ RAL code ² incl. optical losses

Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); specially computed foil for asymmetrical light distribution; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3 24V; photobiological safety according to IEC 62471 risk group RG 1 - low Risk; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

