FINA SUPPORT spot line 30°

011-0303018M

Project / Type

Notes

Count / Date

Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; precise radiation characteristic with 32°x46° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

General

Showcase , Standing
rotation 360°
black , RAL 9021 [1]
IP20
Interior
432 lm
optical inset 80 lm/W[2]

LED

3000 K
CRI ≥ 95
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R_g: 102 , R_f: 94 , $R_{(1-15)}$: 95
MR 0.61
MDER 0.55

Optical

medium
beam angle 32°x46°

Electrical

excl. driver
24 V
fixture 8.0 W
fixture 54 lm/W[3]
optical inset 5.4 W
PC3
24 V

Physical

length 400 mm
width 9 mm
height 9 mm

[1] RAL code
[2] OPTICAL INSET: incl. consideration of optical losses
[3] FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions

['011-0303018M'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com