



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



**General**

Showcase , Standing \_\_\_\_\_

rotation 360° \_\_\_\_\_

white aluminium , RAL 9006 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

1020 lm \_\_\_\_\_

1320 lm/m \_\_\_\_\_

optical inset 92 lm/W<sup>2</sup> \_\_\_\_\_

**LED**

4000 K \_\_\_\_\_

CRI ≥ 97 \_\_\_\_\_

L85 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 96 , R<sub>f(1-15)</sub>: 98 \_\_\_\_\_

MR 0.86 \_\_\_\_\_

MDER 0.78 \_\_\_\_\_

**Optical**

asymmetric \_\_\_\_\_

**Electrical**

excl. driver \_\_\_\_\_

24 V \_\_\_\_\_

fixture 14.6 W \_\_\_\_\_

fixture 70 lm/W<sup>3</sup> \_\_\_\_\_

optical inset 11.1 W \_\_\_\_\_

PC3 \_\_\_\_\_

19 W/m \_\_\_\_\_

24 V \_\_\_\_\_


**Physical**

length 800 mm \_\_\_\_\_

width 9 mm \_\_\_\_\_

height 9 mm \_\_\_\_\_

**Light distribution**



**Product drawing**



<sup>1</sup> RAL code

<sup>2</sup> OPTICAL INSET: incl. consideration of optical losses

<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

**Installation instructions**

