



Project / Type

Notes

Count / Date




General
Showcase , Standing
rotation 360°
white aluminium , RAL 9006 ¹
IP20
Interior
651 lm
1140 lm/m
optical inset 73 lm/W ²

LED
3000 K
CRI ≥ 97
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 99 , R _f : 96 , R _{f(1-15)} : 97
MR 0.68
MDER 0.61

Optical
Opal
opal (lambertsch)

Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



Electrical
excl. driver
24 V
fixture 11.6 W
optical inset 8.9 W
PC3
20 W/m
24 V

Physical
length 600 mm
width 9 mm
height 9 mm

¹ RAL code
² OPTICAL INSET: incl. consideration of optical losses

Installation instructions

