



Project / Type


Notes

Count / Date



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3 24V; photobiological safety according to IEC 62471 risk group RG 1 - low Risk; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase , Standing

rotation 360°

white aluminium , RAL9006 ¹

IP20

Interior

1060 lm

LED

4000 K

CRI ≥ 95

L80 / 50000 h

photobio. safety RG 1 - low Risk

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_r: 92 , R₍₁₋₁₅₎: 89

MR 0.76

MDER 0.69

Optical

asymmetric

Electrical

excl. driver

24 V

system 20.3 W

PC3 24V

inset 78 lm/W²

21 W/m

24 V

Physical

length 1000 mm

width 9 mm

height 9 mm

¹ RAL code ² incl. optical losses

Installation instructions

