



Project / Type _____

Notes _____

Count / Date _____



General

Showcase , Standing
 rotation 360°
 white aluminium , RAL 9006 ¹
 IP20
 Interior
 511 lm
 1370 lm/m
 optical inset 92 lm/W²

LED

4000 K
 CRI ≥ 97
 L85 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 100 , R_f: 96 , R_{f(1-15)}: 98
 MR 0.86
 MDER 0.78

Optical

asymmetric

Electrical

excl. driver
 24 V
 fixture 7.3 W
 fixture 70 lm/W³
 optical inset 5.5 W
 PC3
 20 W/m
 24 V

Physical

length 400 mm
 width 9 mm
 height 9 mm

¹ RAL code

² OPTICAL INSET: incl. consideration of optical losses


³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); specially computed foil for asymmetrical light distribution; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

