



Project / Type

Notes

Count / Date



General
Showcase , Standing
rotation 360°
black , RAL9021 <sup>1</sup>
1350 lm/m
IP20
Interior
233 lm

LED
3000 K
CRI ≥ 97
L85 / 50000 h
photobio. safety RG 1 - low Risk
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 99 , R <sub>f</sub> : 96 , R <sub>f(1-15)</sub> : 97
MR 0.68
MDER 0.61

Optical
asymmetric

Electrical
excl. driver
24 V
system 3.6 W
PC3 24V
inset 84 lm/W <sup>2</sup>
21 W/m
24 V

Physical
length 200 mm
width 9 mm
height 9 mm


<sup>1</sup> RAL code <sup>2</sup> incl. optical losses

Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); specially computed foil for asymmetrical light distribution; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3 24V; photobiological safety according to IEC 62471 risk group RG 1 - low Risk; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

