



Project / Type

Notes

Count / Date



General
Showcase , Standing
rotation 360°
white aluminium , RAL9006 ¹
1350 lm/m
IP20
Interior
233 lm

LED
3000 K
CRI ≥ 97
L85 / 50000 h
initial MacAdam ≤ 3 SDCM


Optical
lead

Electrical
excl. driver
24 V
3.6 W
PC3 24V
65 lm/W
21 W/m
24 V

Physical
length 200 mm
width 9 mm
height 9 mm

¹ RAL code

Light distribution



Product drawing



Installation instructions





Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.979	0.955	0.931	0.908	0.885
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Mounting accessories

MOUNTING POLE L

TYPE	COLOUR	ARTICLE NUMBER(S)
mechanical 180	white aluminium	011-9121116
mechanical 180	black	011-9121118
mechanical / electrical 180	white aluminium	011-9121126
mechanical / electrical 180	black	011-9121128
feeder / mechanical 180	white aluminium	011-9121136
feeder / mechanical 180	black	011-9121138
mechanical 200	white aluminium	011-9121216
mechanical 200	black	011-9121218
mechanical / electrical 200	white aluminium	011-9121226
mechanical / electrical 200	black	011-9121228
feeder / mechanical 200	white aluminium	011-9121236
feeder / mechanical 200	black	011-9121238
mechanical 300	white aluminium	011-9121316
mechanical 300	black	011-9121318
mechanical / electrical 300	white aluminium	011-9121326
mechanical / electrical 300	black	011-9121328
feeder / mechanical 300	white aluminium	011-9121336
feeder / mechanical 300	black	011-9121338



Mounting accessories

MOUNTING POLE T

TYPE	COLOUR	ARTICLE NUMBER(S)
mechanical 180	white aluminium	011-9122116
mechanical 180	black	011-9122118
mechanical / electrical 180	white aluminium	011-9122126
mechanical / electrical 180	black	011-9122128
feeder / mechanical 180	white aluminium	011-9122136
feeder / mechanical 180	black	011-9122138
mechanical 200	white aluminium	011-9122216
mechanical 200	black	011-9122218
mechanical / electrical 200	white aluminium	011-9122226
mechanical / electrical 200	black	011-9122228
feeder / mechanical 200	white aluminium	011-9122236
feeder / mechanical 200	black	011-9122238
mechanical 300	white aluminium	011-9122316
mechanical 300	black	011-9122318
mechanical / electrical 300	white aluminium	011-9122326
mechanical / electrical 300	black	011-9122328
feeder / mechanical 300	white aluminium	011-9122336
feeder / mechanical 300	black	011-9122338





Project / Type

Notes

Count / Date

Mounting accessories

MOUNTING POLE Y

TYPE	COLOUR	ARTICLE NUMBER(S)
mechanical 180	white aluminium	011-9123116
mechanical / electrical 180	white aluminium	011-9123126
mechanical / electrical 180	black	011-9123128
feeder / mechanical 180	white aluminium	011-9123136
feeder / mechanical 180	black	011-9123138
mechanical 200	white aluminium	011-9123216
mechanical 200	black	011-9123218
mechanical / electrical 200	white aluminium	011-9123226
mechanical / electrical 200	black	011-9123228
feeder / mechanical 200	white aluminium	011-9123236
feeder / mechanical 200	black	011-9123238
mechanical 300	white aluminium	011-9123316
mechanical 300	black	011-9123318
mechanical / electrical 300	white aluminium	011-9123326
mechanical / electrical 300	black	011-9123328
feeder / mechanical 300	white aluminium	011-9123336
feeder / mechanical 300	black	011-9123338



Electrical accessories

POWER SUPPLY 24V EU

L·W·H (MM)	ARTICLE NUMBER(S)
130-43-30	011-9212110
195-43-30	011-9212210
220-43-30	011-9212310
130-43-30	011-9212130
195-43-30	011-9212230
220-43-30	011-9212330



POWER SUPPLY 24V UL

L·W·H (MM)	ARTICLE NUMBER(S)
153-41-32	011-9282110
210-40-30	011-9282210
250-40-30	011-9282310
176-45-32	011-9282320
176-45-32	011-9282330



Electrical accessories

EXTENSION CABLE

TYPE	ARTICLE NUMBER(S)
1 × socket / 1 × plug	011-9222120
1 × socket / 1 × plug	011-9222140
1 × socket / 1 × plug	011-9222180