



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



### General

Showcase , Recessed  
 black , RAL 9021<sup>1</sup>  
 IP20  
 Interior  
 1500 lm  
 1280 lm/m  
 optical inset 91 lm/W<sup>2</sup>

### LED

4000 K  
 CRI ≥ 97  
 L85 / 50000 h  
 initial MacAdam ≤ 3 SDCM  
 R<sub>g</sub>: 100 , R<sub>f</sub>: 96 , R<sub>f(1-15)</sub>: 98  
 MR 0.86  
 MDER 0.78

### Optical

asymmetric

### Electrical

excl. driver  
 24 V  
 fixture 21.8 W  
 fixture 69 lm/W<sup>3</sup>  
 optical inset 16.5 W  
 PC3  
 19 W/m  
 24 V

### Physical

length 1200 mm  
 width 9 mm  
 height 9 mm


<sup>1</sup> RAL code

<sup>2</sup> OPTICAL INSET: incl. consideration of optical losses

<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Miniature linear light inset made of aluminium; tubular design; surface lacquered in black; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); specially computed foil for asymmetrical light distribution; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

### Light distribution



### Product drawing



### Installation instructions

