



Project / Type


Notes

Count / Date




Miniature linear light inset made of aluminium; tubular design; surface lacquered in white aluminium; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 97$ ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase , Recessed

white aluminium , RAL 9006 <sup>1</sup>

IP20

Interior

1310 lm

1120 lm/m

optical inset 79 lm/W<sup>2</sup>

LED

4000 K

CRI  $\geq 97$

L85 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 96 , R<sub>f(1-5)</sub>: 98

MR 0.86

MDER 0.78

Optical

Opal

opal (lambertsch)

Electrical

excl. driver

24 V

fixture 21.8 W

optical inset 16.5 W

PC3

19 W/m

24 V

Physical

length 1200 mm

width 9 mm

height 9 mm

<sup>1</sup> RAL code

<sup>2</sup> OPTICAL INSET: incl. consideration of optical losses

Installation instructions

