



Project / Type

Notes

Count / Date



General

Showcase , Standing

rotation 360°

black , RAL9021 <sup>1</sup>

IP20

Interior

573 lm

LED

3000 K

CRI ≥ 95

L80 / 50000 h

photobio. safety RG 1 - low Risk

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 102 , R<sub>r</sub>: 94 , R<sub>(1-15)</sub>: 95

MR 0.61

MDER 0.55

Optical

asymmetric

Electrical

excl. driver

24 V

system 12.0 W

PC3 24V

inset 71 lm/W<sup>2</sup>

22 W/m

24 V

Physical

length 600 mm

width 9 mm

height 9 mm


<sup>1</sup> RAL code <sup>2</sup> incl. optical losses

Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3 24V; photobiological safety according to IEC 62471 risk group RG 1 - low Risk; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

