



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



General

Showcase , Standing \_\_\_\_\_

rotation 360° \_\_\_\_\_

black , RAL 9021 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

422 lm \_\_\_\_\_

optical inset 78 lm/W<sup>2</sup> \_\_\_\_\_

LED

4000 K \_\_\_\_\_

CRI ≥ 95 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 92 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.76 \_\_\_\_\_

MDER 0.69 \_\_\_\_\_

Optical

asymmetric \_\_\_\_\_

Electrical

excl. driver \_\_\_\_\_

24 V \_\_\_\_\_

fixture 8.1 W \_\_\_\_\_

fixture 52 lm/W<sup>3</sup> \_\_\_\_\_

optical inset 5.4 W \_\_\_\_\_

PC3 \_\_\_\_\_

23 W/m \_\_\_\_\_

24 V \_\_\_\_\_

Physical


length 400 mm \_\_\_\_\_

width 9 mm \_\_\_\_\_

height 9 mm \_\_\_\_\_

Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



<sup>1</sup> RAL code

<sup>2</sup> OPTICAL INSET: incl. consideration of optical losses

<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions

