



Project / Type

Notes

Count / Date



General
Showcase , Recessed
white aluminium , RAL 9006 <sup>1</sup>
IP20
Interior
199 lm
1150 lm/m
optical inset 72 lm/W <sup>2</sup>

LED
3000 K
CRI ≥ 97
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 99 , R <sub>r</sub> : 96 , R <sub>t1-15</sub> : 97
MR 0.68
MDER 0.61


Optical
Opal
opal (lambertsch)

Electrical
excl. driver
24 V
fixture 3.6 W
fixture 55 lm/W <sup>3</sup>
optical inset 2.8 W
PC3
21 W/m
24 V

Physical
length 200 mm
width 9 mm
height 9 mm

Miniature linear light inset made of aluminium; tubular design; surface lacquered in white aluminium; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



<sup>1</sup> RAL code

<sup>2</sup> OPTICAL INSET: incl. consideration of optical losses

<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions

