



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



### General

Showcase , Recessed  
 black , RAL9021 <sup>1</sup>  
 1550 lm/m  
 IP20  
 Interior  
 230 lm

### LED

4000 K  
 CRI ≥ 95  
 L80 / 50000 h  
 photobio. safety RG 1 - low Risk  
 initial MacAdam ≤ 3 SDCM  
 R<sub>g</sub>: 99 , R<sub>r</sub>: 92 , R<sub>(1-15)</sub>: 89  
 MR 0.76  
 MDER 0.69

### Optical

asymmetric

### Electrical

excl. driver  
 24 V  
 system 4.8 W  
 PC3 24V  
 inset 72 lm/W<sup>2</sup>  
 32 W/m  
 24 V

### Physical

length 200 mm  
 width 9 mm  
 height 9 mm


<sup>1</sup> RAL code <sup>2</sup> incl. optical losses

### Installation instructions



Miniature linear light inset made of aluminium; tubular design; surface lacquered in black; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); fitted with LED light points; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3 24V; photobiological safety according to IEC 62471 risk group RG 1 - low Risk; accessories are listed separately; light source replaceable by an authorized professional;

### Light distribution



### Product drawing

