



Project / Type _____

Notes _____

Count / Date _____



General

Showcase , Recessed
 black , RAL9021 ¹
 1400 lm/m
 IP20
 Interior
 208 lm

LED

3000 K
 CRI ≥ 95
 L80 / 50000 h
 photobio. safety RG 1 - low Risk
 initial MacAdam ≤ 3 SDCM
 R_g: 102 , R_r: 94 , R₍₁₋₁₅₎: 95
 MR 0.61
 MDER 0.55

Optical

asymmetric _____

Electrical

excl. driver
 24 V
 system 4.8 W
 PC3 24V
 inset 65 lm/W²
 32 W/m
 24 V

Physical

length 200 mm
 width 9 mm
 height 9 mm


¹ RAL code ² incl. optical losses

Installation instructions



Miniature linear light inset made of aluminium; tubular design; surface lacquered in black; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3 24V; photobiological safety according to IEC 62471 risk group RG 1 - low Risk; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

