

FINA SUPPORT opal 30°

011-13060160



Project / Type _____

Notes _____

Count / Date _____



General

Showcase , Standing _____

rotation 360° _____

white aluminium , RAL9006 ¹ _____

1050 lm/m _____

IP20 _____

Interior _____

1020 lm _____

LED

3000 K _____

CRI ≥ 97 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

Optical

Opal _____

opal _____

Electrical

excl. driver _____

24 V _____

18.2 W _____

PC3 24V _____

56 lm/W _____

19 W/m _____

24 V _____

Physical

length 1000 mm _____

width 9 mm _____

height 9 mm _____


¹ RAL code

Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3 24V; accessories are listed separately;

Light distribution



Product drawing

