

# FINA SUPPORT opal 30°

011-1306116O



Project / Type


Notes

Count / Date



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 97$ ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3 24V; accessories are listed separately;

## Light distribution



## Product drawing



### General

Showcase , Standing

rotation 360°

white aluminium , RAL9006 <sup>1</sup>

1150 lm/m

IP20

Interior

1110 lm

### LED

4000 K

CRI  $\geq 97$

L85 / 50000 h

initial MacAdam  $\leq 3$  SDCM

### Optical

Opal

opal

### Electrical

excl. driver

24 V

18.2 W

PC3 24V

61 lm/W

19 W/m

24 V

### Physical

length 1000 mm

width 9 mm

height 9 mm

<sup>1</sup> RAL code

## Installation instructions



[011-1306116O] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · [www.xal.com](http://www.xal.com)