

# FINA SUPPORT opal 30°


011-13041180



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Showcase , Standing \_\_\_\_\_  
rotation 360° \_\_\_\_\_  
black , RAL9021 <sup>1</sup> \_\_\_\_\_  
1250 lm/m \_\_\_\_\_  
IP20 \_\_\_\_\_  
Interior \_\_\_\_\_  
714 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_  
CRI ≥ 97 \_\_\_\_\_  
L85 / 50000 h \_\_\_\_\_  
initial MacAdam ≤ 3 SDCM \_\_\_\_\_

## Optical

Opal \_\_\_\_\_  
opal \_\_\_\_\_

## Electrical

excl. driver \_\_\_\_\_  
24 V \_\_\_\_\_  
11.6 W \_\_\_\_\_  
PC3 24V \_\_\_\_\_  
62 lm/W \_\_\_\_\_  
20 W/m \_\_\_\_\_  
24 V \_\_\_\_\_

## Physical

length 600 mm \_\_\_\_\_  
width 9 mm \_\_\_\_\_  
height 9 mm \_\_\_\_\_


<sup>1</sup> RAL code

## Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3 24V; accessories are listed separately;

## Light distribution



## Product drawing

