

# FINA SUPPORT opal 30°

011-13050160



Project / Type


Notes

Count / Date




Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 97$ ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

## Light distribution



## Product drawing



### General

Showcase , Standing

rotation 360°

white aluminium , RAL9006 <sup>1</sup>

IP20

Interior

814 lm

### LED

3000 K

CRI  $\geq 97$

L85 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 96 , R<sub>t(1-15)</sub>: 97

MR 0.68

MDER 0.61

### Optical

Opal

opal (lambertsch)

### Electrical

excl. driver

24 V

system 14.6 W

PC3

inset 73 lm/W<sup>2</sup>

19 W/m

24 V

### Physical

length 800 mm

width 9 mm

height 9 mm

<sup>1</sup> RAL code  
<sup>2</sup> SYSTEM: incl. consideration of optical losses and the efficiency of the operating device. INSET: incl. consideration of optical losses.

## Installation instructions

