

MITA circle 200 reflector

trim

074-8123138R



Project / Type	
Notes	
Count / Date	



General

Ceiling , Recessed	
black , RAL 9005 ¹	
Reflector chrome	
IP20	
1700 lm	

LED

4000 K	
CRI ≥ 90	
L90 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R _g : 99 , R _r : 92 , R _{t(1-15)} : 90	
MR 0.81	
MDER 0.74	

Optical

Reflector	
symmetric	
UGR < 19 , ≥65° <1500 cd/m ²	
PstLM ≤ 1.0 ²	
SVM ≤ 0.4 ²	

Electrical

DALI-2	
220-240 V	
system 13.2 W	
system 129 lm/W ³	
PC2	

Physical


diameter 210 mm	
height 36 mm	

Cutout


diameter 200 mm	
min. ceiling thickness 2 mm	
max. ceiling thickness 25 mm	
recessed depth 62 mm	

¹ RAL code ² Value of containing product at full load (undimmed)
³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Light distribution



Product drawing



Installation instructions



Lighting calculator

