

MITA circle 450 reflector

direct

suspended
074-7611138R



Project / Type

Notes

Count / Date



| |
|-------------------------------|
| General |
| Ceiling , Suspended |
| black , RAL 9005 ¹ |
| Reflector chrome |
| IP20 |
| 3920 lm |


| |
|---|
| LED |
| 4000 K |
| CRI ≥ 90 |
| L90 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| R _g : 99 , R _r : 92 , R _{t(1-15)} : 90 |
| MR 0.81 |
| MDER 0.74 |

| |
|---|
| Optical |
| Reflector |
| symmetric |
| UGR ≤ 19 , ≥65° <1500 cd/m ² |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |


Ring-shaped light fitting in die-cast aluminium; extremely slim design; surface black powder coated; suspended luminaire with adjustable pendant rod mounting (chrome) 1000mm, feed in rod; electronic operating unit installed in the canopy; blind cover to cover the cut-out, held by magnet, available as an accessory; accessories are listed separately; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high gloss reflector with faceted design; Reflector chrome; UGR ≤ 19; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

| |
|------------------------------|
| Electrical |
| DALI-2 |
| 220-240 V |
| system 30 W |
| system 131 lm/W ³ |
| PC1 |
| 1 DALI Addr. |

Light distribution



Product drawing



| |
|-----------------|
| Physical |
| diameter 426 mm |
| height 38 mm |

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator

