

# BO 32

PROFILES 40 2 lamps

042-0610137F



Project / Type

Notes

Count / Date



## General

Ceiling , Semi-Recessed

tilt max 90°

rotation 360°

RAL Traffic white , RAL 9016 <sup>1</sup>

IP20

1610 lm

## LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 97 , R<sub>f</sub>: 90 , R<sub>(1-15)</sub>: 89

MR 0.81

MDER 0.74

## Optical

flood

beam angle 37°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2

220-240 V

system 20.6 W

system 78 lm/W<sup>3</sup>

PC1

1 DALI Addr.

## Physical

length 300 mm

width 32 mm

height 128 mm

0.45 kg

adapter300 mm

## Cutout

diameter 54 mm

min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 110 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.


## Installation instructions



## Lighting calculator



## Light distribution



flood 37°

h (m)	EO° (lx)	ø (m)
1	4450	0.67
2	1110	1.34
3	490	2.01
4	280	2.68
5	180	3.35

## Product drawing

