

# FINA SUPPORT spot line

## 30°

011-0305016S



Project / Type

Notes

Count / Date



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 95$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3 24V; accessories are listed separately; light source replaceable by an authorized professional;

### Product drawing



#### General

Showcase , Standing

rotation 360°

white aluminium , RAL9006 <sup>1</sup>

IP20

Interior

#### LED

3000 K

CRI  $\geq 95$

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 102 , R<sub>f</sub>: 94 , R<sub>f(1-15)</sub>: 95

MR 0.61

MDER 0.55

#### Optical

spot

#### Electrical

excl. driver

24 V

PC3 24V

24 V

#### Physical

length 800 mm

width 9 mm

height 9 mm

<sup>1</sup> RAL code

### Installation instructions

