

FINA SUPPORT spot line

011-0206016S



Project / Type _____

Notes _____

Count / Date _____



General

Showcase , Standing
rotation 360°
white aluminium , RAL9006 ¹
IP20
Interior

LED

3000 K
CRI ≥ 95
photobio. safety RG 1 - low Risk
initial MacAdam ≤ 3 SDCM
R_g: 102 , R_f: 94 , R_{f(1-15)}: 95
MR 0.61
MDER 0.55

Optical

spot

Electrical

excl. driver
24 V
PC3 24V
24 V

Physical

length 1000 mm
width 9 mm
height 9 mm

¹ RAL code

Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3 24V; photobiological safety according to IEC 62471 risk group RG 1 - low Risk; accessories are listed separately; light source replaceable by an authorized professional;

Product drawing

