



Project / Type

Notes

Count / Date



Miniature linear light inset made of aluminium; tubular design; surface lacquered in white aluminium; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3 24V; photobiological safety according to IEC 62471 risk group RG 1 - low Risk; accessories are listed separately; light source replaceable by an authorized professional;

Product drawing



General

Showcase , Recessed

white aluminium , RAL9006 ¹

IP20

Interior

LED

3000 K

CRI ≥ 95

photobio. safety RG 1 - low Risk

initial MacAdam ≤ 3 SDCM

R_g: 102 , R_f: 94 , R₍₁₋₁₅₎: 95

MR 0.61

MDER 0.55

Optical

spot

Electrical

excl. driver

24 V

PC3 24V

24 V

Physical

length 600 mm

width 9 mm

height 9 mm

¹ RAL code

Installation instructions

