



Project / Type _____

Notes _____

Count / Date _____



General

Showcase , Recessed _____

white aluminium , RAL9006 ¹ _____

IP20 _____

Interior _____

LED

4000 K _____

CRI ≥ 95 _____

photobio. safety RG 1 - low Risk _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 , R_f: 92 , R₍₁₋₁₅₎: 89 _____

MR 0.76 _____

MDER 0.69 _____

Optical

spot _____

Electrical

excl. driver _____

24 V _____

PC3 24V _____

24 V _____

Physical

length 400 mm _____

width 9 mm _____

height 9 mm _____

Miniature linear light inset made of aluminium; tubular design; surface lacquered in white aluminium; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); fitted with LED light points; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3 24V; photobiological safety according to IEC 62471 risk group RG 1 - low Risk; accessories are listed separately; light source replaceable by an authorized professional;

Product drawing



¹ RAL code

Installation instructions

