

MICROPRISMATIC UGR < 22

MOVE IT PRO

086-6110930 086-6010000P



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track _____

1470 lm/m _____

IP20 _____

1470 lm _____

LED

2700 K _____

CRI \geq 90 _____

L90 / 50000 h _____

initial MacAdam \leq 3 SDCM _____

R_g: 101 , R_f: 90 , R_{f(1-15)}: 88 _____

MR 0.51 _____

MDER 0.46 _____

Optical

Microprismatic _____

microprismatic _____

PstLM \leq 1.0 ¹ _____

SVM \leq 0.4 ¹ _____

Electrical

DALI-2 _____

system 18.2 W _____

PC2 220-240V _____

system 81 lm/W² _____

1 DALI Addr. _____

18 W/m _____

Physical

length 1000 mm _____

width 43 mm _____

height 13 mm _____

¹ Value of containing product at full load (undimmed)


² incl. optical losses and the efficiency of the operating device (converter)

Lighting calculator



Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; power supplied via MOVE IT PRO system track profile; completely homogeneously illuminated, microprismatic PMMA cover; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2 220-240V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing

