

MICROPRISMATIC UGR < 22

MOVE IT PRO

086-6110930 086-6010000P



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track _____

1470 lm/m _____

IP20 _____

1470 lm _____

LED

2700 K _____

CRI \geq 90 _____

L90 / 50000 h _____

initial MacAdam \leq 3 SDCM _____

R_g: 101 , R_f: 90 , R_{f(1-15)}: 88 _____

MR 0.51 _____

MDER 0.46 _____

Optical

Microprismatic _____

microprismatic _____

PstLM \leq 1.0 ¹ _____

SVM \leq 0.4 ¹ _____

Electrical

DALI-2 _____

system 18.2 W _____

PC2 220-240V _____

system 81 lm/W² _____

1 DALI Addr. _____

18 W/m _____

Physical

length 1000 mm _____

width 43 mm _____

height 13 mm _____

¹ Value of containing product at full load (undimmed)


² incl. optical losses and the efficiency of the operating device (converter)

Lighting calculator



Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; power supplied via MOVE IT PRO system track profile; completely homogeneously illuminated, microprismatic PMMA cover; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2 220-240V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



MICROPRISMATIC UGR < 22

MOVE IT PRO
086-6110930 086-6010000P



Project / Type _____

Notes _____

Count / Date _____

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.94	0.92	0.9
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a Room Surface Maintenance Factor		
MF	Maintenance Factor		LLMF Lamp Lumens Maintenance Factor		
LMF ^a	Luminaire Maintenance Factor		LSF Lamp Survival Faktor		

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	17
B13	22
B16	28
C10	22
C13	27
C16	35

Components

MICROPRISMATIC COVER

L-W-H (MM)	ARTICLE NUMBER(S)
1000-43-5	086-6010000P

Mounting accessories

END CAPS

TYPE	COLOUR	ARTICLE NUMBER(S)
1 pair	traffic white	086-6091117
1 pair	jet black	086-6091118

Optical accessories

CONTINUOUS MICROPRISMATIC COVER

L-W-H (MM)	ARTICLE NUMBER(S)
6000-43-5	086-6080600P
25000-43-5	086-6082500P

