


# MOVE IT 25 / 45

## ACOUSTIC double grid

inlay  
050-231321S



Project / Type	
Notes	
Count / Date	



<b>General</b>
Luminaire / Track , Mounted
limestone


<b>Physical</b>
panel only for NODE connector + track 1210 mm
length 2435 mm
width 1235 mm
height 25 mm
2.2 kg

<b>Acoustics</b>
Alpha w ( $\alpha_w$ ) up to 1 <sup>1</sup>
SAC (sound absorption class) up to A <sup>1</sup>
NRC up to 1.3 <sup>1</sup>
SAA up to 1.32 <sup>1</sup>

<sup>1</sup> Acoustic data calculations based on MOVE IT 25/45 acoustic square grid inlay, cavity 40cm

Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; rectangular design; high quality visual and tactile surface with embossed pattern, limestone; foreign fiber inclusions possible; absorption of direct sound and sound reflected from the ceiling; this creates high acoustic performance; for installation in the MOVE IT 25 / 45 suspended system composed of node connectors and profiles; subsequent insertion in already installed MOVE IT suspended system possible; installation without tools;

### Product drawing



# MOVE IT 25 / 45

## ACOUSTIC double grid

inlay  
050-231321S



Project / Type

Notes

Count / Date

### Equivalent sound absorption area ( $A_{eq}$ )

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
1.3	2.73	3.2	4.1	4.97	5.23

### Sound absorption coefficient ( $\alpha_p$ )

