



048-2622017S 048-2696317 002-90742



Ceiling , Recessed  
tilt max 30°  
rotation 360°  
white , RAL 9016 <sup>1</sup>  
Mounting set traffic white  
front IP40 , back IP20  
908 lm  
fixture 84 lm/W<sup>2</sup>

3000 K
CRI $\geq 90$
initial MacAdam $\leq 2$ SDCM
R <sub>g</sub> : 99, R <sub>f</sub> : 90, R <sub>{f(1-15)}</sub> : 87
MR 0.6
MDER 0.54

spot
beam angle 15°
UGR < 19
PstLM ≤ 1.0 <sup>3</sup>
SVM ≤ 0.4 <sup>3</sup>

non DIM
220-240 V
system 12.8 W
fixture 10.9 W
36 Vf
300 mA
PC2

trim
diameter 80 mm
height 48 mm
0.21 kg

diameter 73 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 60 mm

<sup>1</sup> RAL code  
<sup>2</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses  
 SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.  
<sup>3</sup> Value of containing product at full load (undimmed)

# SASSO 60 round adjustable

trim  
048-2622017S 048-2696317 002-90742



Project / Type

Notes

Count / Date

Installation instructions



Lighting calculator

