

MINO CIRCLE ACOUSTIC

1500

inlay
034-270211S



Project / Type

Notes

Count / Date



General

Luminaire / Track , Mounted

limestone

Physical

diameter 1434 mm

height 24 mm

7.1 kg

Acoustics

Alpha w (α_w) up to 0.65

SAC (sound absorption class) up to C

NRC up to 0.7

SAA up to 0.74


Acoustic data calculations based on MINO CIRCLE ACOUSTIC 1000, cavity 100cm

Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50% post-consumer recycled PET; round design; high quality visual and tactile surface, limestone; colour may deviate; absorption of direct sound and sound reflected from the ceiling; this creates high acoustic performance; for insertion into the MINO 60 CIRCLE 1500 ceiling or MINO 60 CIRCLE 1500 suspended;

Product drawing



MINO CIRCLE ACOUSTIC 1500

inlay
034-270211S



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

| 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ |
|--------|--------|--------|---------|---------|---------|
| 0.97 | 1.2 | 1.83 | 2.67 | 3.07 | 3.3 |

Sound absorption coefficient (a_p)

