

# MINO CIRCLE ACOUSTIC 1000

inlay  
034-270111S



Project / Type

Notes

Count / Date



General

Luminaire / Track , Mounted

limestone

Physical

diameter 937 mm

height 24 mm

2.09 kg

Acoustics

Alpha w ( $\alpha_w$ ) up to 0.65

SAC (sound absorption class) up to C

NRC up to 0.7

SAA up to 0.74


Acoustic data calculations based on MINO CIRCLE ACOUSTIC 1000, cavity 100cm

## Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50% post-consumer recycled PET; round design; high quality visual and tactile surface, limestone; colour may deviate; absorption of direct sound and sound reflected from the ceiling; this creates high acoustic performance; for insertion into the MINO 60 CIRCLE 1000 ceiling or MINO 60 CIRCLE 1000 suspended;

## Product drawing



# MINO CIRCLE ACOUSTIC 1000

inlay

034-270111S



Project / Type

Notes

Count / Date

## Equivalent sound absorption area ( $A_{eq}$ )

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.5	0.5	0.87	1.3	1.43	1.57

## Sound absorption coefficient ( $\alpha_p$ )

